



Symbol	Label	Image	QTY	Manufacturer	Catalog	Description	Number Lamps	Lamp Output	LLF	Input Power	Polar Plot
	D		2	Lithonia Lighting	WDGE2 LED P2 40K 70CRI T3M	WDGE2 LED WITH P2 - PERFORMANCE PACKAGE, 4000K, 70CRI, TYPE 3 MEDIUM OPTIC	1	2327	0.87	18.9815	 Max: 1706cd
	I		4	Lithonia Lighting	RSX1 LED P2 40K R5	RSX Area Fixture Size 1 P2 Lumen Package 4000K CCT Type R5 Distribution	1	10106	0.92	72.95	 Max: 3861cd
	K		4	Lithonia Lighting	LBR4 ALO1 (750LM) SWW1 (4000K) AR LSS WD 80CRI	4 INCH LBR DOWNLIGHT 750LM 4000K CLEAR SEMI-SPECULAR WIDE 80 CRI	1	849	0.8	9	 Max: 697cd

Statistics						
Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
Future Parking 1	+	1.3 fc	1.4 fc	1.1 fc	1.3:1	1.2:1
Future Parking 2	+	1.0 fc	1.4 fc	0.7 fc	2.0:1	1.4:1
Parking	+	1.3 fc	3.2 fc	0.5 fc	6.4:1	2.6:1
Property Line	+	0.0 fc	0.0 fc	0.0 fc	N/A	N/A
Drive Through	+	6.1 fc	7.8 fc	4.9 fc	1.6:1	1.2:1

Plan View
Scale - 1" = 20'